

Food slicer

Characteristics

Food sliced from (ri = right; le = left)

Full metal construction

Metal construction

High-quality plastic

Silver metallic

White

Supply table inclined

Foldable supply table

Suspended construction

Floor panel made of shatterproof glass

Feet made of steel

Circular blade, 17 cm Ø

Circular blade cover

Serrated blade

Slice thickness adjustable up to approx. mm

Safety switch for intermittent and continuous operation

Two-finger switch-on safety system

Vario electronic rpm adjustment

Easy-going carriage

Metal carriage

Plastic carriage

Carriage detachable

Carriage way approx. cm

Food tray

Cable compartment

Eco-motor

DC motor

Watt

Duty cycle in min.

selected design

	elexa ⁷	amido ³
	ri	ri
Full metal construction	•	•
Metal construction		
High-quality plastic		
Silver metallic	•	•
White		
Supply table inclined		•
Foldable supply table	•	
Suspended construction		
Floor panel made of shatterproof glass		
Feet made of steel		
Circular blade, 17 cm Ø	•	•
Circular blade cover		•
Serrated blade	•	•
Slice thickness adjustable up to approx. mm	14	23
Safety switch for intermittent and continuous operation		•
Two-finger switch-on safety system	•	
Vario electronic rpm adjustment		
Easy-going carriage		•
Metal carriage	•	•
Plastic carriage		
Carriage detachable	•	•
Carriage way approx. cm	20	24
Food tray	•	•
Cable compartment	•	•
Eco-motor	•	•
DC motor		
Watt	65	65
Duty cycle in min.	5	5

premium

	secura ⁹	sinus ⁵
	ri	ri
Full metal construction	•	•
Metal construction		
High-quality plastic		
Silver metallic	•	•
White		
Supply table inclined	•	
Foldable supply table		
Suspended construction		•
Floor panel made of shatterproof glass		•
Feet made of steel		
Circular blade, 17 cm Ø	•	•
Circular blade cover	•	•
Serrated blade	•	•
Slice thickness adjustable up to approx. mm	23	23
Safety switch for intermittent and continuous operation	•	•
Two-finger switch-on safety system		
Vario electronic rpm adjustment	•	
Easy-going carriage	•	
Metal carriage	•	
Plastic carriage		•
Carriage detachable	•	•
Carriage way approx. cm	24	24
Food tray	•	
Cable compartment	•	•
Eco-motor		•
DC motor	•	
Watt	130	65
Duty cycle in min.	10	5

comfort

	unica ³	varido ¹	sinus ¹
	ri	ri	ri
Full metal construction	•	•	
Metal construction			•
High-quality plastic			
Silver metallic	•	•	•
White			
Supply table inclined	•	•	
Foldable supply table			
Suspended construction			•
Floor panel made of shatterproof glass			•
Feet made of steel	•		
Circular blade, 17 cm Ø	•	•	•
Circular blade cover			
Serrated blade	•	•	•
Slice thickness adjustable up to approx. mm	20	20	20
Safety switch for intermittent and continuous operation			•
Two-finger switch-on safety system	•	•	
Vario electronic rpm adjustment			
Easy-going carriage			
Metal carriage			
Plastic carriage	•	•	•
Carriage detachable	•	•	•
Carriage way approx. cm	18	18	18
Food tray		•	
Cable compartment		•	
Eco-motor	•	•	•
DC motor			
Watt	65	65	65
Duty cycle in min.	5	5	5

economy

	arcus ³	fino ¹	orbis ⁵	orbis ¹
	ri	ri	ri	ri
Full metal construction		•		
Metal construction	•	•		
High-quality plastic			•	•
Silver metallic	•	•		
White			•	•
Supply table inclined	•			
Foldable supply table			•	•
Suspended construction				
Floor panel made of shatterproof glass				
Feet made of steel				
Circular blade, 17 cm Ø	•	•	•	•
Circular blade cover				
Serrated blade	•	•	•	•
Slice thickness adjustable up to approx. mm	18	20	18	18
Safety switch for intermittent and continuous operation	•	•	•	•
Two-finger switch-on safety system				
Vario electronic rpm adjustment			•	
Easy-going carriage				
Metal carriage				
Plastic carriage	•	•	•	•
Carriage detachable	•	•	•	•
Carriage way approx. cm	18	18	18	18
Food tray	•	•		
Cable compartment	•	•	•	•
Eco-motor	•	•	•	•
DC motor				
Watt	65	65	65	65
Duty cycle in min.	5	5	5	5